

Product Specification

F200

HIGH PERFORMANCE GNSS RECEIVER



GNSS Performance		
Channels		1408
Satellites tracking	GPS	L1C/A, L1C, L1P, L2C, L2P(Y), L5
	BDS	B1I, B2I, B3I, B1C, B2a, B2b, ACEBOC
	GLONASS	L1, L2, L3
	GALILEO	E1, E5a, E5b, ALTBOC, E6
	QZSS	L1, L2, L5
	NavIC	L5
	SBAS	WAAS, GAGAN, MSAS, EGNOS, SDCM, BDS
L-Band		B2b PPP (Only for the Asian-Pacific region)
Static		- H: 2.5 mm + 0.5 ppm (RMS) - V: 5.0 mm + 0.5 ppm (RMS)
RTK		- H: 8 mm + 1.0 ppm (RMS) - V: 15 mm + 1.0 ppm (RMS)
Correction data		RTCM V3.X, RTCM2.X, CMR
Data output		GGA, ZDA, GSA, GSV, GST, VTG, RMC, GLL, Binary

Tilt sensor	
Tilt survey	8 mm + 0.3 mm / degree
Degree	up to 60°
Update rate	400Hz

Data Interface	
TNC	Connect internal radio with antenna
Type-C	Data transmission or charge
Update rate	400Hz
5-pin port	- Connect to external radio & external power - NMEA output
SIM card	√
Supported band	Supported LTE-cat1 LTE FDD: B1/B2/B3/B4/B5/B7/B8/B18/B19/B20/B25/B26/B28 LTE TDD: B34/B38/B39/B40/B41 GSM: 850/900/1800/1900

System	
OS	Linux
Internal memory	8 GB
Bluetooth	BT5.0+EDR, BLE
Wi-Fi	802.11 b/g/n
Web UI	Supported

Internal Radio	
Type	TX & RX
Emitting power	1W
Operation range	3-5 km typically1
Frequency range	410 - 470 MHz
Channel spacing	6.25 KHz / 12.5 KHz / 25 KHz
Protocol	TRIMTALK 450s, TRIMTALK, TRIMMK III, PCC-GMSK, PCC-4FSK, SOUTH, TRANSEOT, GEOTALK, GEOMARK, SATEL, HITARGET, HZSZ, PCCFST, PCCEOT_ADL, SATEL_ADL

Physical	
Dimension	Φ152 mm × 92 mm
Weight	945 g
Operating temperature	-30 C ~ 60 C
Storage temperature	-40 C ~ 80 C
Water / dust proof	IP67
Humidity	up to 100%
Battery	Built-in, Lithium-ion battery, 3.6V DC/1200mAh
Voltage	5-pin: 15V DC, 2A Type-C: PD 12V DC, 1.5A
Working time	up to 24 hours as rover mode
Indicators	Satellites, datalink, power, Bluetooth
Button	Power button, function button
Voice	Supported

1: It varies with the obstacle and terrain.